

**ACMI #5395**  
**WATERBASED**  
**FLEXOGRAPHIC**

Description:

ACMI #5395 was formulated as a medium fast drying waterbased flexographic ink for asphalt roofing material.

**SPECIFICATIONS:**

Applications: Flexographic printing

Viscosity: 60 - 75 seconds, #2 Zahn

Specific Gravity: 1.07

Weight per Gallon: 8.9 lbs.

Flashpoint: None

Dry time: Medium fast

Variations in temperature and humidity may affect dry time.

Shelf Life & Storage: Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.

Protect this ink from freezing.

Chemical Base: Water

Colorant Base: Pigment

**RECONDITIONER:** #5306 Reconditioner (clear in color)

**CLEANER:** #5305 Cleaner (blue in color)

**COLORS:** Orange, White

**AVAILABILITY:** Pints, Quarts and Gallons

Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

***American Coding and Marking Ink Co. Inc.***

1220 North Avenue, Plainfield, NJ 07062

**Phone:** 908-756-0373 **Fax:** 908-756-0570 **Web Site:** [www.americancoding.com](http://www.americancoding.com)