

ACMI #6
STAMP PAD INK
CARTON CODING
CARTON PRINTING

Description: ACMI #6 was formulated for marking paper, corrugated, wood and other porous substrates from a stamp pad, flexographic printer, or other printing method using rubber type. Pad life is excellent and dry time is fast. This ink can also be used for inline carton coding and ink roll impregnating.

SPECIFICATIONS:

Applications: Foam stamp pad, flexographic printer, or other method using rubber type, inline carton coder

Viscosity: 50 cps

Specific Gravity: 1.19

Weight per Gallon: 9.92 lbs.

Flashpoint: >200° F.

Dry time: 2-4 seconds

Variations in temperature and humidity may affect dry time.

Shelf Life & Storage: Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.

Chemical Base: Water

Colorant Base: Dye

RECONDITIONER: #6 Reconditioner

COLORS: Black, Violet, Blue, Yellow, Green, Gold, Orange, Brown, Red

AVAILABILITY: Pints, Quarts and Gallons

Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

American Coding and Marking Ink Co. Inc.

1220 North Avenue, Plainfield, NJ 07062

Phone: 908-756-0373 **Fax:** 908-756-0570 **Web Site:** www.americancoding.com