

ACMI #754
STENCIL INK
NONPOROUS

Description:

ACMI #754 was formulated for stenciling on coated fiber drums. The ink will not ghost or skid on material after marking.

SPECIFICATIONS:

Applications: Fiber drum coder with X-firm neoprene ink roller or stencil roller ,
Coated fiber drums

Viscosity: 44 cps

Specific Gravity: 1.0

Weight per Gallon: 8.34 lbs.

Flashpoint: 53° F.

Dry time: 5 minutes

Variations in temperature and humidity may affect dry time.

Shelf Life & Storage: Use within 1 year is recommended. Ink should be stored at normal room temperature and capped tightly after each use.

Chemical Base: Solvent

Colorant Base: Pigment (NL)

RECONDITIONER: #150 Reconditioner

COLORS: White, Black

AVAILABILITY: Pints, Quarts and Gallons

Smaller sizes available on request

STATEMENT OF LIABILITY

Neither the manufacturer nor the seller shall be liable for any injury, loss or damage arising out of the use of this product. The only obligations of the manufacturer or the seller shall be to replace any quantity of this product found to be defective or, at the option of the seller or manufacturer, to refund the purchase price. The purchaser or user of this product should, before use of the product, determine whether it is suitable for that use. The user assumes all risk and liability in connection with that use.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED

American Coding and Marking Ink Co. Inc.

1220 North Avenue, Plainfield, NJ 07062

Phone: 908-756-0373 **Fax:** 908-756-0570 **Web Site:** www.americancoding.com